AKOMO BAFFLE

High-performance acoustic baffle for ceiling applications

NRC ≈ 1.10
αw ≈ 1.00 (Class A – ISO 11654)
Aeq ≈ 0,78 m^2

KEY BENEFITS



- Lightweight and quick installation
- 360° sound absorption for maximum efficiency
- High absorption efficiency thanks to dual-sided performance
- Modular and scalable system
- Flexible positioning for optimal acoustic performance
- Sleek architectural design, seamlessly integrated into any interior

ACOUSTIC PERFORMANCE – with an air gap of 200 mm

Hz	125	250	500	1000	2000	4000
Aeq	0.17	0.48	0.78	0.87	0.87	0.87

TECHNICAL SPECIFICATIONS

Type:	Linear acoustic absorber (baffle)
Dimensions:	1200 x 220 x 50 mm
Material:	Acoustic foam (9 kg/m^3)
Structure:	Open cell
Fire class:	EN13501-1: C s2 d0 | DIN4102 B1
Colours:	White | Light grey | Dark grey
Service range:	-43°C to +150°C
Optional finish:	Flock coating

APPLICATION

Designed for offices, meeting rooms, production environments, as well as hospitality and public spaces, the Akomo Baffle improves acoustic comfort by reducing reverberation. Freely suspended in the space, it absorbs sound from all directions and enhances speech intelligibility.

www.akomo.eu
Wittestraat 1 | B-8501 Kortrijk-Heule | Belgium

BASF's Basotect® EcoBalanced partner